

				
Consumo	80W	100W	100W	200W
Índice de protección	IP65	IP65	IP65	IP65
Vataje / Consumo led	Epistar	Epistar	Epistar	Bridgelux
Instalaciones HM	240W	300W	300W	600W
Lumen	6400LM ±10%	8000LM ±10%	8000LM ±10%	15660Lux ±10%
Lux a 1m	2603 Lux	TBA Lux	TBA Lux	2405 Lux
Temperatura de color	5000-6000K	5000-6000K	5000-6000K	5000-6000K
Voltaje de entrada / Gama de frecuencias	90-240VAC 50-60Hz	90-240VAC 50-60Hz	90-240VAC 50-60Hz	85-265VAC 50-60Hz
Factor de potencia	>0.95 PF	>0.95 PF	>0.95 PF	>0.95 PF
CRI	Ra >80	Ra >80	Ra >80	Ra >70
Angulo	75°	75°	75°	120°
Temperatura de trabajo	-40°C+50°C	-40°C+50°C	-40°C+50°C	-40°C+55°C
Duración de vida	30,000hrs	30,000hrs	30,000hrs	30,000hrs
Materiales	Aluminium Alloy + Glass Cover	Aluminium Alloy + Glass Cover	Aluminium Alloy + Glass Cover	Aluminium Alloy + Glass Cover
Colores de carcasa	Standard is Grey, also in Black or White	Standard is Grey, also in Black or White	Standard is Grey, also in Black or White	Standard is Grey, also in Black or White
Distorsión armónica	20%	20%	20%	20%
Dimensiones	443x371x115mm	443x371x115mm	443x371x115mm	560x510x170mm
Peso	8.75 KG	8.75 KG	8.75 KG	13.5 KG